



Downhole Pump Specifications List



| Specifications | | | | | | STATOR | | | | | | | | CASING | | | | | |
|----------------|-------------|-----------------------------------|-----------------------|------------------|----------|-----------------------|-------------------------------|----------------|--------------------------|--------------------------|--|--------------------------|-----------------|------------------|--------------------------|--------------------------|-----------|---|---------------|
| Stator Size | Model | Displacement | | Lifting Capacity | | Max. speed [rpm] | Recommended Spacing [mm] | O.D. [mm] | Pipe bore size [mm] | Thread API 5B | Coupling O.D. [mm] | P _s [mm] | Stages [1] | Length [mm] | D _r [mm] | P _r [mm] | Dimension | Weight lb/ft | |
| | | m ³ /day at 100 rpm | bls/day at 100 rpm | [m] | [feet] | | | | | | | | | | | | | | |
| 166 | TW 0.7-900 | 0.7 | 4.5 | 900 | 3000 | 500 | 30 | 52.17 | 40 | 1.66" NUE | 52.2 ⁽²⁾ | 54 | 20 | 1080 | 1.66" NUE | 19 | 27 | 3-1/2 ⁽²⁾ | 17.05 |
| | TW 0.7-1200 | 0.7 | 4.5 | 1200 | 4000 | | | 52.17 | 40 | | | 54 | 27 | 1458 | | 19 | 27 | | |
| | TW 0.7-1500 | 0.7 | 4.5 | 1500 | 5000 | | 50 | 52.17 | 40 | | | 54 | 34 | 1836 | | 19 | 27 | | |
| | TW 0.7-1800 | 0.7 | 4.5 | 1800 | 6000 | | | 52.17 | 40 | | | 54 | 40 | 2160 | | 19 | 27 | | |
| | TW 0.7-2000 | 0.7 | 4.5 | 2000 | 6600 | | | 52.17 | 40 | | | 54 | 45 | 2430 | | 19 | 27 | | |
| | TW 0.7-2400 | 0.7 | 4.5 | 2400 | 8000 | | 30 | 52.17 | 40 | | | 54 | 54 | 2916 | | 19 | 27 | | |
| | TW 1-900 | 1 | 6.3 | 900 | 3000 | | | 52.17 | 40 | | | 60 | 20 | 1200 | | 20 | 30 | | |
| | TW 1-1200 | 1 | 6.3 | 1200 | 4000 | | 50 | 52.17 | 40 | | | 60 | 27 | 1620 | | 20 | 30 | | |
| | TW 1-1500 | 1 | 6.3 | 1500 | 5000 | | | 52.17 | 40 | | | 60 | 34 | 2040 | | 20 | 30 | | |
| | TW 1-1800 | 1 | 6.3 | 1800 | 6000 | | | 52.17 | 40 | | | 60 | 40 | 2400 | | 20 | 30 | | |
| | TW 1-2000 | 1 | 6.3 | 2000 | 6600 | | 50 | 52.17 | 40 | | | 60 | 45 | 2700 | | 20 | 30 | | |
| TW 1-2400 | 1 | 6.3 | 2400 | 8000 | 52.17 | 40 | | 60 | 54 | 3240 | 20 | 30 | | | | | | | |
| 238 | TW 1.5-900 | 1.5 | 10 | 900 | 3000 | 500 | 30 | 73.0 | 57.0 | 2-3/8" EUE or 2-3/8" NUE | 77.8 ⁽¹⁾ or 73 ⁽²⁾ | 50 | 20 | 1000 | 2-3/8" EUE or 2-3/8" NUE | 31 | 25 | 3-1/2 ⁽²⁾ or 4-1/2 ⁽¹⁾⁽²⁾ | 9.2 - or 15.1 |
| | TW 1.5-1200 | 1.5 | 10 | 1200 | 4000 | | | 73.0 | 57.0 | | | 50 | 27 | 1350 | | 31 | 25 | | |
| | TW 1.5-1500 | 1.5 | 10 | 1500 | 5000 | | 50 | 73.0 | 57.0 | | | 50 | 34 | 1700 | | 31 | 25 | | |
| | TW 1.5-1800 | 1.5 | 10 | 1800 | 6000 | | | 73.0 | 57.0 | | | 50 | 40 | 2000 | | 31 | 25 | | |
| | TW 1.5-2000 | 1.5 | 10 | 2000 | 6600 | | | 73.0 | 57.0 | | | 50 | 45 | 2250 | | 31 | 25 | | |
| | TW 1.5-2400 | 1.5 | 10 | 2400 | 8000 | | 30 | 73.0 | 57.0 | | | 50 | 54 | 2700 | | 31 | 25 | | |
| | TW 3-900 | 3 | 19 | 900 | 3000 | | | 73.0 | 57.0 | | | 80 | 20 | 1600 | | 27.1 | 40 | | |
| | TW 3-1200 | 3 | 19 | 1200 | 4000 | | 50 | 73.0 | 57.0 | | | 80 | 27 | 2160 | | 27.1 | 40 | | |
| | TW 3-1500 | 3 | 19 | 1500 | 5000 | | | 73.0 | 57.0 | | | 80 | 34 | 2720 | | 27.1 | 40 | | |
| | TW 3-1800 | 3 | 19 | 1800 | 6000 | | | 73.0 | 57.0 | | | 80 | 40 | 3200 | | 27.1 | 40 | | |
| | TW 3-2000 | 3 | 19 | 2000 | 6600 | | 50 | 73.0 | 57.0 | | | 80 | 45 | 3600 | | 27.1 | 40 | | |
| | TW 3-2400 | 3 | 19 | 2400 | 8000 | | | 73.0 | 57.0 | | | 80 | 54 | 4320 | | 27.1 | 40 | | |
| | TW 4-900 | 4 | 25 | 900 | 3000 | | 30 | 73.0 | 57.0 | | | 90 | 20 | 1800 | | 28 | 45 | | |
| | TW 4-1200 | 4 | 25 | 1200 | 4000 | | | 73.0 | 57.0 | | | 90 | 27 | 2430 | | 28 | 45 | | |
| | TW 4-1500 | 4 | 25 | 1500 | 5000 | | | 73.0 | 57.0 | | | 90 | 34 | 3060 | | 28 | 45 | | |



Downhole Pump Specifications List



| Specifications | | | | | | STATOR | | | | | | | | CASING | | | | | | |
|----------------|------------|-----------------------------------|-----------------------|------------------|----------|-----------------------|-------------------------------|--------|----------------|------------------------|--|----------------|--------|--------|--------------------------|--------------------------|-----------|--|---------------|----|
| Stator Size | Model | Displacement | | Lifting Capacity | | Max. speed [rpm] | Recommended Spacing [mm] | O.D. | Pipe bore size | Thread API 5B | Coupling O.D. [mm] | P _s | Stages | Length | D _r [mm] | P _r [mm] | Dimension | Weight lb/ft | | |
| | | m ³ /day at 100 rpm | bls/day at 100 rpm | [m] | [feet] | | | [mm] | [mm] | | | [mm] | [] | [mm] | | | | | | |
| 238 | TW 4-1800 | 4 | 25 | 1800 | 6000 | 500 | 50 | 73.0 | 57.0 | 2-3/8"EUE or 2-3/8"NUE | 77.8(1) or 73(2) | 90 | 40 | 3600 | 2-3/8"EUE or 2-3/8"NUE | 28 | 45 | 3-1/2"(2) or 4-1/2"(1)(2) | 9.2 - or 15.1 | |
| | TW 4-2000 | 4 | 25 | 2000 | 6600 | | | 73.0 | 57.0 | | | 90 | 45 | 4050 | | 28 | 45 | | | |
| | TW 4-2400 | 4 | 25 | 2400 | 8000 | | | 73.0 | 57.0 | | | 90 | 54 | 4860 | | 28 | 45 | | | |
| | TW 6-900 | 6 | 38 | 900 | 3000 | | | 30 | 73.0 | | | 57.0 | 96 | 20 | | 1920 | 32 | | | 48 |
| | TW 6-1200 | 6 | 38 | 1200 | 4000 | | | | 73.0 | | | 57.0 | 96 | 27 | | 2592 | 32 | | | 48 |
| | TW 6-1500 | 6 | 38 | 1500 | 5000 | | | 50 | 73.0 | | | 57.0 | 96 | 34 | | 3264 | 32 | | | 48 |
| | TW 6-1800 | 6 | 38 | 1800 | 6000 | | | | 73.0 | | | 57.0 | 96 | 40 | | 3840 | 32 | | | 48 |
| | TW 6-2000 | 6 | 38 | 2000 | 6600 | | | | 73.0 | | | 57.0 | 96 | 45 | | 4320 | 32 | | | 48 |
| TW 6-2400 | 6 | 38 | 2400 | 8000 | 73.0 | 57.0 | 96 | | 54 | 5184 | 32 | 48 | | | | | | | | |
| 278 | TW 7-900 | 7 | 44 | 900 | 3000 | 500 | 30 | 89 | 71 | 2-7/8"EUE or 2-7/8"NUE | 93 ⁽¹⁾ or 88.9 ⁽²⁾ | 90 | 20 | 1800 | 2-7/8"EUE or 2-7/8"NUE | 37.5 | 45 | 4-1/2 ⁽¹⁾ or 4-1/2 ⁽²⁾ | 11.6 or 15.1 | |
| | TW 7-1200 | 7 | 44 | 1200 | 4000 | | | 89 | 71 | | | 90 | 27 | 2430 | | 37.5 | 45 | | | |
| | TW 7-1500 | 7 | 44 | 1500 | 5000 | | 50 | 89 | 71 | | | 90 | 34 | 3060 | | 37.5 | 45 | | | |
| | TW 7-1800 | 7 | 44 | 1800 | 6000 | | | 89 | 71 | | | 90 | 40 | 3600 | | 37.5 | 45 | | | |
| | TW 7-2000 | 7 | 44 | 2000 | 6600 | | | 89 | 71 | | | 90 | 45 | 4050 | | 37.5 | 45 | | | |
| | TW 7-2400 | 7 | 44 | 2400 | 8000 | | | 89 | 71 | | | 90 | 54 | 4860 | | 37.5 | 45 | | | |
| | TW 10-900 | 10 | 63 | 900 | 3000 | | 30 | 89 | 71 | | | 110 | 20 | 2200 | | 40 | 55 | | | |
| | TW 10-1200 | 10 | 63 | 1200 | 4000 | | | 89 | 71 | | | 110 | 27 | 2970 | | 40 | 55 | | | |
| | TW 10-1500 | 10 | 63 | 1500 | 5000 | | 50 | 89 | 71 | | | 110 | 34 | 3740 | | 40 | 55 | | | |
| | TW 10-1800 | 10 | 63 | 1800 | 6000 | | | 89 | 71 | | | 110 | 40 | 4400 | | 40 | 55 | | | |
| | TW 10-2000 | 10 | 63 | 2000 | 6600 | | | 89 | 71 | | | 110 | 45 | 4950 | | 40 | 55 | | | |
| | TW 10-2400 | 10 | 63 | 2400 | 8000 | | | 89 | 71 | | | 110 | 54 | 5940 | | 40 | 55 | | | |
| | TW 15-900 | 15 | 100 | 900 | 3000 | | 30 | 89 | 71 | | | 150 | 20 | 3000 | | 42 | 75 | | | |
| | TW 15-1200 | 15 | 100 | 1200 | 4000 | | | 89 | 71 | | | 150 | 27 | 4050 | | 42 | 75 | | | |
| | TW 15-1500 | 15 | 100 | 1500 | 5000 | | 50 | 89 | 71 | | | 150 | 34 | 5100 | | 42 | 75 | | | |
| | TW 15-1800 | 15 | 100 | 1800 | 6000 | | | 89 | 71 | | | 150 | 40 | 6000 | | 42 | 75 | | | |
| | TW 15-2000 | 15 | 100 | 2000 | 6600 | | | 89 | 71 | | | 150 | 45 | 6750 | | 42 | 75 | | | |
| | TW 15-2400 | 15 | 100 | 2400 | 8000 | | | 89 | 71 | | | 150 | 54 | 8100 | | 42 | 75 | | | |



Downhole Pump Specifications List



| Specifications | | | | | | STATOR | | | | | | | | CASING | | | | | |
|----------------|--------------|-----------------------------------|-----------------------|------------------|----------|-----------------------|-------------------------------|----------------|--------------------------|------------------------|--|--------------------------|-----------------|------------------|--------------------------|--------------------------|-----------|------------------------------------|------------------|
| Stator Size | Model | Displacement | | Lifting Capacity | | Max. speed [rpm] | Recommended Spacing [mm] | O.D. [mm] | Pipe bore size [mm] | Thread API 5B | Coupling O.D. [mm] | P _s [mm] | Stages [1] | Length [mm] | D _r [mm] | P _r [mm] | Dimension | Weight lb/ft | |
| | | m ³ /day at 100 rpm | bls/day at 100 rpm | [m] | [feet] | | | | | | | | | | | | | | |
| 350 | TW 16.5-900 | 16.5 | 104 | 900 | 3000 | 500 | 30 | 108 | 90 | 3-1/2"EUE or 3-1/2"NUE | 114.3 ⁽¹⁾ or 107.95 ⁽²⁾ | 150 | 20 | 3000 | 3-1/2"EUE or 3-1/2"NUE | 52 | 75 | 5" (2) or 1-1/2" (1) or 5-1/2" (2) | 13 or 20 or 26.8 |
| | TW 16.5-1200 | 16.5 | 104 | 1200 | 4000 | | | 108 | 90 | | | 150 | 27 | 4050 | | 52 | 75 | | |
| | TW 16.5-1500 | 16.5 | 104 | 1500 | 5000 | | 50 | 108 | 90 | | | 150 | 34 | 5100 | | 52 | 75 | | |
| | TW 16.5-1800 | 16.5 | 104 | 1800 | 6000 | | | 108 | 90 | | | 150 | 40 | 6000 | | 52 | 75 | | |
| | TW 16.5-2000 | 16.5 | 104 | 2000 | 6600 | | | 108 | 90 | | | 150 | 45 | 6750 | | 52 | 75 | | |
| | TW 16.5-2400 | 16.5 | 104 | 2400 | 8000 | | | 108 | 90 | | | 150 | 54 | 8100 | | 52 | 75 | | |
| | TW 20-900 | 20 | 126 | 900 | 3000 | | 30 | 108 | 90 | | | 164 | 20 | 3280 | | 53 | 82 | | |
| | TW 20-1200 | 20 | 126 | 1200 | 4000 | | | 108 | 90 | | | 164 | 27 | 4428 | | 53 | 82 | | |
| | TW 20-1500 | 20 | 126 | 1500 | 5000 | | 50 | 108 | 90 | | | 164 | 34 | 5576 | | 53 | 82 | | |
| | TW 20-1800 | 20 | 126 | 1800 | 6000 | | | 108 | 90 | | | 164 | 40 | 6560 | | 53 | 82 | | |
| | TW 20-2000 | 20 | 126 | 2000 | 6600 | | | 108 | 90 | | | 164 | 45 | 7380 | | 53 | 82 | | |
| | TW 20-2400 | 20 | 126 | 2400 | 8000 | | | 108 | 90 | | | 164 | 54 | 8856 | | 53 | 82 | | |
| | TW 25-900 | 25 | 158 | 900 | 3000 | | 30 | 108 | 90 | | | 180 | 20 | 3600 | | 54 | 90 | | |
| | TW 25-1200 | 25 | 158 | 1200 | 4000 | | | 108 | 90 | | | 180 | 27 | 4860 | | 54 | 90 | | |
| | TW 25-1500 | 25 | 158 | 1500 | 5000 | | 50 | 108 | 90 | | | 180 | 34 | 6120 | | 54 | 90 | | |
| | TW 25-1800 | 25 | 158 | 1800 | 6000 | | | 108 | 90 | | | 180 | 40 | 7200 | | 54 | 90 | | |
| | TW 25-2000 | 25 | 158 | 2000 | 6600 | | | 108 | 90 | | | 180 | 45 | 8100 | | 54 | 90 | | |
| | TW 25-2400 | 25 | 158 | 2400 | 8000 | | | 108 | 90 | | | 180 | 54 | 9720 | | 54 | 90 | | |
| 350 | TW 35-900 | 35 | 221 | 900 | 3000 | 400 | 30 | 114 | 96 | 3-1/2"EUE | 120.65 ⁽¹⁾ or 127.00 ⁽²⁾ | 210 | 20 | 4200 | 4"EUE or 4"NUE | 60 | 105 | 6-5/8" (1) or 5-1/2" (2) | 32 or 20 |
| | TW 35-1200 | 35 | 221 | 1200 | 4000 | | | 114 | 96 | | | 210 | 27 | 5670 | | 60 | 105 | | |
| | TW 35-1500 | 35 | 221 | 1500 | 5000 | | 50 | 114 | 96 | | | 210 | 34 | 7140 | | 60 | 105 | | |
| | TW 35-1800 | 35 | 221 | 1800 | 6000 | | | 114 | 96 | | | 210 | 40 | 8400 | | 60 | 105 | | |
| | TW 35-2000 | 35 | 221 | 2000 | 6600 | | | 114 | 96 | | | 210 | 45 | 9450 | | 60 | 105 | | |
| | TW 35-2400 | 35 | 221 | 2400 | 8000 | | | 114 | 96 | | | 210 | 54 | 11340 | | 60 | 105 | | |
| | TW 40-900 | 40 | 252 | 900 | 3000 | | 30 | 114 | 96 | | | 216 | 20 | 4320 | | 61 | 108 | | |
| | TW 40-1200 | 40 | 252 | 1200 | 4000 | | | 114 | 96 | | | 216 | 27 | 5832 | | 61 | 108 | | |



Downhole Pump Specifications List



| Specifications | | | | | | STATOR | | | | | | | | CASING | | | | | |
|----------------|-------------|-----------------------------------|-----------------------|------------------|----------|-----------------------|-------------------------------|----------------|--------------------------|------------------|-------------------------|--------------------------|-----------------|------------------|--------------------------|--------------------------|-----------|--------------------------|----------|
| Stator Size | Model | Displacement | | Lifting Capacity | | Max. speed [rpm] | Recommended Spacing [mm] | O.D. [mm] | Pipe bore size [mm] | Thread API 5B | Coupling O.D. [mm] | P _s [mm] | Stages [1] | Length [mm] | D _r [mm] | P _r [mm] | Dimension | Weight lb/ft | |
| | | m ³ /day at 100 rpm | bls/day at 100 rpm | [m] | [feet] | | | | | | | | | | | | | | |
| 350 | TW 40-1500 | 40 | 252 | 1500 | 5000 | 400 | 50 | 114 | 96 | 3-1/2"EU | 120.65(1) or 127.00(2) | 216 | 34 | 7344 | 4"EU or 4"NUE | 61 | 108 | 6-5/8" (1) or 5-1/2" (2) | 32 or 20 |
| | TW 40-1800 | 40 | 252 | 1800 | 6000 | | | 114 | 96 | | | 216 | 40 | 8640 | | 61 | 108 | | |
| | TW 40-2000 | 40 | 252 | 2000 | 6600 | | | 114 | 96 | | | 216 | 45 | 9720 | | 61 | 108 | | |
| | TW 50-900 | 50 | 315 | 900 | 3000 | | 30 | 114 | 96 | | | 260 | 20 | 5200 | | 61.5 | 130 | | |
| | TW 50-1200 | 50 | 315 | 1200 | 4000 | | | 114 | 96 | | | 260 | 27 | 7020 | | 61.5 | 130 | | |
| | TW 50-1500 | 50 | 315 | 1500 | 5000 | | 50 | 114 | 96 | | | 260 | 34 | 8840 | | 61.5 | 130 | | |
| | TW 50-1800 | 50 | 315 | 1800 | 6000 | | | 114 | 96 | | | 260 | 40 | 10400 | | 61.5 | 130 | | |
| | TW 60-900 | 60 | 378 | 900 | 3000 | | 30 | 114 | 96 | | | 300 | 20 | 6000 | | 65 | 150 | | |
| | TW 60-1200 | 60 | 378 | 1200 | 4000 | | | 114 | 96 | | | 300 | 27 | 8100 | | 65 | 150 | | |
| TW 60-1500 | 60 | 378 | 1500 | 5000 | 50 | 114 | 96 | 300 | 34 | 10200 | 65 | 150 | | | | | | | |
| 400 | TW 75-900 | 75 | 473 | 900 | 3000 | 300 | 30 | 121 | 99 | 4"EU or 4"NUE | 141.3 | 310 | 20 | 6200 | 4-1/2"EU | 67 | 155 | 6-5/8" | 32 |
| | TW 75-1200 | 75 | 472 | 1200 | 4000 | | | 121 | 99 | | | 310 | 27 | 8370 | | 67 | 155 | | |
| | TW 75-1500 | 75 | 473 | 1500 | 5000 | | 50 | 121 | 99 | | | 310 | 34 | 10540 | | 67 | 155 | | |
| | TW 75-1800 | 75 | 473 | 1800 | 6000 | | | 121 | 99 | | | 310 | 40 | 12400 | | 67 | 155 | | |
| | TW 80-900 | 80 | 504 | 900 | 3000 | | 30 | 121 | 99 | | | 324 | 20 | 6480 | | 68 | 162 | | |
| | TW 80-1200 | 80 | 504 | 1200 | 4000 | | | 121 | 99 | | | 324 | 27 | 8748 | | 68 | 162 | | |
| | TW 80-1500 | 80 | 504 | 1500 | 5000 | | | 121 | 99 | | | 324 | 34 | 11016 | | 68 | 162 | | |
| 450 | TW 120-900 | 120 | 757 | 900 | 3000 | 300 | 30 | 140 | 120 | 4-1/2"EU | 141.3 | 380 | 20 | 7600 | 4-1/2"EU | 79 | 190 | | |
| | TW 120-1200 | 120 | 757 | 1200 | 4000 | | | 140 | 120 | | | 380 | 27 | 10260 | | 79 | 190 | | |
| | TW 120-1500 | 120 | 757 | 1500 | 5000 | | | 140 | 120 | | | 380 | 34 | 12920 | | 79 | 190 | | |

⁽¹⁾ Stator material NBRH, Stop-pin included

⁽²⁾ Rotor material 1.7225 with Cr-coating, 150µm

245, 6025- 12th Street SE, Calgary, AB T2H 2K1 Canada
 Tel: 1-(403)-543-0350 Fax: 1-(403)-543-0351
 Email: canam@canamservices.com
www.canamservices.com

