



Evenwall PC Pump Sizes

MODEL NUMBER	Manufacture part number	Canam part number	Collar O.D. (mm)	Collar Thread (mm-API)	Rotor Thread (mm-API rod)	Overall Length (cm)
EW 4-1200 rotor	36.3052.1355	K363052			22 MM	161.1
EW 4-1200 stator	51.8047.00	K518047	93.2	73 MM		174
EW 7-1200 rotor	36.30531355	K363053			22MM	212.6
EW 7-1200 stator	51.8048.00	K518048	93.2	73 MM		226
STD 10-1200	36.30761355	K363076			22MM	380
STD 10-1200	51.3764.00	K513764	114.3	89MM		386.5
EW 10-1200 rotor	36.30751455	K363075			22MM	209.1
EW 10-1200	51.8092.00	K518092	114.3	89 MM		219
EW 10-1800 rotor	36.30581355	K363058			22 MM	381.1
EW 10-1800	51.8054.00	K518054	114.3	89 MM		390
STD 15-1000	35.35081245	K353508			22 MM	354
STD 15-1000	51.3760.00	K513760	114.3	89 MM		352
STD 15-1400	35.35091245	K353509			22MM	469
STD 15-1400	51.3759.00	K513759	114.3	89 MM		475
EW 15-1400 rotor	35.35121245	K353512			22 MM	284
EW 15-1400	51.8093.00	K518093	114.3	89 MM		292
STD 28-1200	35.35111245	K353511			22 MM	479
STD 28-1200	51.3762.00	K513762	127	101.6 MM		479
EW 30-900 rotor	36.30551355	K363055			22 MM	263.6
EW 30-900 stator	51.8050.00	K518050	114.3	89 MM		278
EW 60-900 rotor	35.35101245	K353510			25 MM	324
EW 60-900 stator	51.8052.00	K518052	127	101.6 MM		341
EW 60-600 stator	51-8050.00	K518050	127	101.6 MM		227
EW 60-600- rotor	35.35101243	K351024			25MM	212